

PERFORMANCE DATA—LIGHT COMMERCIAL



900, 990 Supply Registers

PERFORMANCE BASED ON NOMINAL SIZES SHOWN IN BOLD

			NC-20				NC-30				NC-40		
Nom. Duct Size (in.)	Nom. Duct Area (ft ²)	Core Area (ft ²)	Core Vel.	300	400	500	600	700	800	1000	1200	1400	
			Vel. Press.	0.006	0.010	0.016	0.022	0.031	0.040	0.062	0.090	0.122	
			0°	0.016	0.029	0.046	0.066	0.090	0.117	0.183	0.263	0.358	
			Total	22.5°	0.018	0.033	0.051	0.074	0.100	0.131	0.204	0.294	
			Press.	45°	0.028	0.049	0.077	0.111	0.152	0.198	0.309	0.445	0.606
6x6	0.25	0.19	cfm	57	76	95	114	133	152	190	228	266	
			NC	-	-	-	15	20	24	31	36	41	
			0°	5-7-14	7-10-16	8-12-18	10-14-20	12-15-21	13-16-23	15-18-25	16-20-28	17-21-30	
			Throw (ft)	22.5° 4-6-11	5-8-12	6-10-14	8-11-15	9-12-16	10-12-18	11-14-20	12-15-22	13-16-23	
8x6	0.33	0.26	cfm	78	104	130	156	182	208	260	312	364	
			NC	-	-	11	17	21	25	32	38	42	
			0°	5-9-16	8-12-19	10-15-21	12-16-23	14-18-25	15-19-27	17-21-30	19-23-32	20-25-35	
			Throw (ft)	22.5° 4-7-13	6-9-15	8-11-16	9-13-18	11-14-19	12-15-21	13-16-23	15-18-25	16-19-27	
10x6	0.42	0.34	cfm	102	136	170	204	238	272	340	408	476	
			NC	-	-	12	18	23	27	33	39	43	
			0°	6-10-19	9-13-21	11-17-24	13-19-26	16-20-28	18-21-30	20-24-34	21-26-37	23-28-40	
			Throw (ft)	22.5° 5-8-14	7-10-17	9-13-19	10-14-20	12-16-22	14-17-23	15-19-26	17-20-29	18-22-31	
8x8	0.44	0.37	cfm	111	148	185	222	259	296	370	444	518	
			NC	-	-	13	18	23	27	34	39	44	
			0°	6-10-19	9-14-22	12-17-25	14-19-27	16-21-30	18-22-32	20-25-35	22-27-39	24-30-42	
			Throw (ft)	22.5° 5-8-15	7-11-17	9-13-19	11-15-21	13-16-23	14-17-25	16-19-27	17-21-30	19-23-32	
12x6	0.50	0.41	cfm	123	164	205	246	287	328	410	492	574	
			NC	-	-	13	19	23	27	34	39	44	
			0°	7-11-20	10-15-24	12-18-26	15-20-29	17-22-31	19-24-33	21-26-37	24-29-41	25-31-44	
			Throw (ft)	22.5° 5-8-16	8-11-18	9-14-20	11-16-22	13-17-24	15-18-26	17-20-29	18-22-32	20-24-34	
14x6	0.58	0.48	cfm	144	192	240	288	336	384	480	576	672	
			NC	-	-	14	19	24	28	35	40	45	
			0°	7-12-22	11-16-25	13-20-28	16-22-31	18-24-34	21-25-36	23-28-40	25-31-44	28-34-48	
			Throw (ft)	22.5° 6-9-17	8-12-20	10-15-22	12-17-24	14-18-26	16-20-28	18-22-31	20-24-34	21-26-37	
16x6	0.67	0.57	cfm	171	228	285	342	399	456	570	684	798	
			NC	-	-	15	20	25	29	35	41	45	
			0°	8-13-24	11-17-28	14-22-31	17-24-34	20-26-37	23-28-39	25-31-44	28-34-48	30-37-52	
			Throw (ft)	22.5° 6-10-19	9-13-22	11-17-24	13-19-26	16-20-28	18-22-30	20-24-34	22-26-37	23-28-40	
10x10	0.69	0.59	cfm	177	236	295	354	413	472	590	708	826	
			NC	-	-	15	20	25	29	35	41	46	
			0°	8-13-24	12-18-28	15-22-32	18-24-35	20-26-37	23-28-40	26-32-45	28-35-49	31-37-53	
			Throw (ft)	22.5° 6-10-19	9-14-22	11-17-24	14-19-27	16-20-29	18-22-31	20-24-35	22-27-38	24-29-41	
18x6	0.75	0.63	cfm	189	252	315	378	441	504	630	756	882	
			NC	-	-	15	20	25	29	36	41	46	
			0°	8-14-25	12-18-29	15-23-33	18-25-36	21-27-39	24-29-41	27-33-46	29-36-51	32-39-55	
			Throw (ft)	22.5° 7-11-20	9-14-23	12-18-25	14-20-28	16-21-30	18-23-32	21-25-36	23-28-39	24-30-42	
20x6	0.83	0.72	cfm	216	288	360	432	504	576	720	864	1008	
			NC	-	-	16	21	26	30	36	42	46	
			0°	9-15-27	13-19-31	16-24-35	19-27-38	23-29-41	25-31-44	28-35-49	31-38-54	34-41-58	
			Throw (ft)	22.5° 7-11-21	10-15-24	12-19-27	15-21-30	17-23-32	20-24-34	22-27-38	24-30-42	26-32-45	
22x6	0.92	0.77	cfm	231	308	385	462	539	616	770	924	1078	
			NC	-	-	16	21	26	30	37	42	47	
			0°	9-15-28	13-20-32	17-25-36	20-28-40	23-30-43	26-32-46	29-36-51	32-40-56	35-43-60	
			Throw (ft)	22.5° 7-12-22	10-16-25	13-19-28	16-22-31	18-23-33	20-25-35	23-28-40	25-31-43	27-33-47	
24x6	1.00	0.88	cfm	264	352	440	528	616	704	880	1056	1232	
			NC	-	-	16	22	26	30	37	43	47	
			0°	10-16-30	14-21-34	18-27-39	21-30-42	25-32-46	28-34-49	31-39-55	34-42-60	37-46-65	
			Throw (ft)	22.5° 8-12-23	11-17-27	14-21-30	17-23-33	19-25-35	22-27-38	24-30-42	27-33-46	29-35-50	
30x6	1.25	1.11	cfm	333	444	555	666	777	888	1110	1332	1554	
			NC	-	11	17	23	27	31	38	44	48	
			0°	11-18-34	16-24-39	20-30-43	24-34-47	28-36-51	32-39-55	35-43-61	39-47-67	42-51-72	
			Throw (ft)	22.5° 9-14-26	12-19-30	16-23-34	19-26-37	22-28-40	25-30-42	27-34-47	30-37-52	32-40-56	

Performance notes appear at end of table

PERFORMANCE DATA



900, 990 Supply Registers

PERFORMANCE BASED ON NOMINAL SIZES SHOWN IN BOLD

Nom. Duct Size (in.)	Nom. Duct Area (ft ²)	Core Area (ft ²)	NC-20		NC-30			NC-40			NC-50		
			Core Vel.	300	400	500	600	700	800	1000	1200	1400	
			Vel. Press.	0.006	0.010	0.016	0.022	0.031	0.040	0.062	0.090	0.122	
			0°	0.016	0.029	0.046	0.066	0.090	0.117	0.183	0.263	0.358	
			Total	22.5°	0.018	0.033	0.051	0.074	0.100	0.131	0.204	0.294	0.401
			Press.	45°	0.028	0.049	0.077	0.111	0.152	0.198	0.309	0.445	0.606
42x38	11.08	10.67	cfm		3201	4268	5335	6402	7469	8536	10670	12804	14938
			NC		12	20	27	32	37	41	48	53	58
			Throw	0°	35-56-104	50-74-120	62-93-134	74-104-147	87-112-159	98-120-170	110-134-190	120-147-208	130-159-225
			(ft)	22.5°	27-43-81	38-58-93	48-72-104	58-81-114	67-87-123	76-93-132	85-104-147	93-114-161	101-123-174
			45°	16-25-47	22-34-54	28-42-60	34-47-66	39-51-71	44-54-76	49-60-85	54-66-94	58-71-101	
40x40	11.11	10.7	cfm		3210	4280	5350	6420	7490	8560	10700	12840	14980
			NC		12	20	27	32	37	41	48	53	58
			Throw	0°	35-56-104	50-75-120	62-93-134	75-104-147	87-113-159	98-120-170	110-134-190	120-147-208	130-159-225
			(ft)	22.5°	27-43-81	39-58-93	48-72-104	58-81-114	67-87-123	76-93-132	85-104-147	93-114-161	101-123-174
			45°	16-25-47	22-34-54	28-42-61	34-47-66	39-51-72	44-54-77	49-61-86	54-66-94	58-72-101	
48x36	12.00	11.57	cfm		3471	4628	5785	6942	8099	9256	11570	13884	16198
			NC		12	21	27	33	37	41	48	53	58
			Throw	0°	36-58-108	52-78-125	65-97-140	78-108-153	90-117-165	102-125-177	114-140-198	125-153-217	135-165-234
			(ft)	22.5°	28-45-84	40-60-97	50-75-108	60-84-119	70-91-128	79-97-137	88-108-153	97-119-168	105-128-181
			45°	16-26-49	23-35-56	29-44-63	35-49-69	41-53-74	46-56-80	51-63-89	56-69-97	61-74-105	
42x42	12.25	11.82	cfm		3546	4728	5910	7092	8274	9456	11820	14184	16548
			NC		12	21	27	33	37	41	48	53	58
			Throw	0°	37-59-109	52-78-126	65-98-141	78-109-155	91-118-167	103-126-179	115-141-200	126-155-219	137-167-236
			(ft)	22.5°	28-46-85	40-61-98	51-76-110	61-85-120	71-92-130	80-98-139	89-110-155	98-120-170	106-130-183
			45°	16-26-49	24-35-57	29-44-64	35-49-70	41-53-75	46-57-80	52-64-90	57-70-99	61-75-106	
44x44	13.44	12.99	cfm		3897	5196	6495	7794	9093	10392	12990	15588	18186
			NC		12	21	28	33	38	42	48	54	58
			Throw	0°	38-62-115	55-82-133	68-103-148	82-115-162	96-124-175	108-133-187	121-148-210	133-162-230	143-175-248
			(ft)	22.5°	30-48-89	42-64-103	53-80-115	64-89-126	74-96-136	84-103-145	94-115-162	103-126-178	111-136-192
			45°	17-28-52	25-37-60	31-46-67	37-52-73	43-56-79	49-60-84	54-67-94	60-73-103	64-79-112	
48x42	14.00	13.54	cfm		4062	5416	6770	8124	9478	10832	13540	16248	18956
			NC		13	21	28	33	38	42	49	54	59
			Throw	0°	39-63-117	56-84-135	70-105-151	84-117-166	98-127-179	110-135-191	124-151-214	135-166-234	146-179-253
			(ft)	22.5°	30-49-91	43-65-105	54-81-117	65-91-128	76-98-139	86-105-148	96-117-166	105-128-182	113-139-196
			45°	18-28-53	25-38-61	31-47-68	38-53-75	44-57-81	50-61-86	56-68-96	61-75-105	66-81-114	
46x46	14.69	14.22	cfm		4266	5688	7110	8532	9954	11376	14220	17064	19908
			NC		13	21	28	33	38	42	49	54	59
			Throw	0°	40-64-120	57-86-139	72-107-155	86-120-170	100-130-183	113-139-196	127-155-219	139-170-240	150-183-259
			(ft)	22.5°	31-50-93	44-67-107	56-83-120	67-93-132	78-101-142	88-107-152	98-120-170	107-132-186	116-142-201
			45°	18-29-54	26-39-62	32-48-70	39-54-76	45-58-83	51-62-88	57-70-99	62-76-108	67-83-117	
48x46	15.33	14.85	cfm		4455	5940	7425	8910	10395	11880	14850	17820	20790
			NC		13	22	28	34	38	42	49	54	59
			Throw	0°	41-66-123	59-88-142	73-110-158	88-123-174	102-133-187	116-142-200	129-158-224	142-174-245	153-187-265
			(ft)	22.5°	32-51-95	45-68-110	57-85-123	68-95-134	79-103-145	90-110-155	100-123-174	110-134-190	119-145-205
			45°	18-30-55	26-40-64	33-49-71	40-55-78	46-60-84	52-64-90	58-71-101	64-78-110	69-84-119	
48x48	16.00	15.50	cfm		4650	6200	7750	9300	10850	12400	15500	18600	21700
			NC		13	22	28	34	38	42	49	55	59
			Throw	0°	42-67-125	60-90-145	75-112-162	90-125-177	105-135-192	118-145-205	132-162-229	145-177-251	156-192-271
			(ft)	22.5°	33-52-97	46-70-112	58-87-125	70-97-137	81-105-148	92-112-159	102-125-177	112-137-194	121-148-210
			45°	19-30-56	27-40-65	34-50-73	40-56-80	47-61-86	53-65-92	59-73-103	65-80-113	70-86-122	

- 0°, 22.5° & 45° represent blade deflection angles
- Performance data is based on duct sizes in bold, the performance varies slightly for duct sizes not shown in bold
- See the section, Engineering Guidelines, for drop information when selecting larger supply grilles for cooling purposes
- See the "Performance Notes" portion in this section for notes and correction factors

- See the section, Engineering Guidelines, for catalog throw information
- Each NC value represents the noise criteria curve that will not be exceeded by the sound pressure in any of the octave bands, 2 through 7, with a room absorption of 10 dB, re 10⁻¹² watts