

MODEL R52

ROUND STEEL OPPOSED BLADE DAMPER - Duct Mount Only FOR MODEL 1600 DIFFUSER

STANDARD INDUSTRY TOLERANCES APPLY. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

TOP VIEW VALVES CLOSED

OPPOSED BLADE DAMPER VALVES FULLY OPEN

TENSION PLATE

3/16 HEX OPERATOR ROD (BY OTHERS)

LOCK NUTS: LOOSEN BEFORE ADJUSTING DAMPER. TIGHTEN AFTER ADJUSTING DAMPER TO PROVIDE POSITIVE LOCK.

CROSS SECTION WITH VALVES PARTLY OPEN SHOWING OPPOSED BLADE OPERATION

IF OPERATOR IS TO BE REMOVED AFTER SETTING DAMPER, DO NOT DRIVE INTO TENSION PLATE AS THIS LOCKS ROD IN PLACE FOR PERMANENT INSTALLATION

SIZE	S	O	P
6	5-15/16	1-3/4	3
8	7-15/16	1-3/4	3-1/2
10	9-15/16	1-3/4	4-9/16
12	11-15/16	1-3/4	4-9/16
14	13-15/16	1-3/4	4-9/16
16	15-15/16	1-3/4	4-9/16
18	17-15/16	1-3/4	4-9/16

Steel construction. Standard finish is white.

PROJECT: _____

ARCHITECT: _____

ENGINEER: _____

CONTRACTOR: _____

LOCATION: _____

